

Commercial and Operational Office

P.O. Box 930001 Empire Heights Building Suite 13F-A-01, Business Bay Dubai, United Arab Emirates

> Tel: + 971(4) 551 9930 Fax: +971(4) 551 9931

info@vortexoffshore.com | www.vortexoffshore.com

FAST CREW SUPPLIER 1605

1340 BHP | 30 KTS | 29 PAX



-60-

SPECIFICATIONS:

Fast Pilot Boat / Crew Supplier

GENERAL:

Year Built: 2013, Damen Port of Registry: Doha

Classification: Bureau Veritas
I • Hull • MACH

Special service / Fast Utility Vessel

Sea Area 3

(The navigation notation "Sea area 2" is corresponding to sea areas where Hs > 2.5 m is not to exceed for more than 10% of the year.)

DIMENSIONS:

Length Overall: 16.15 m (including appendages)

Length Moulded: 14.53 m

Beam Overall: 5.40 m (including appendages)

Beam (moulded): 4.54 m

Depth at side: 1.85 m (at half length)
Draught max.: 0.85 m (approx.)

GRT / NRT: 26 T / 8 T

DWT: The total maximum deadweight (fuel, persons,

cargo, etc) should not exceed 4.00 tonnes.

CAPACITIES:

Fuel Oil: $2.00 \text{ m}^3 \text{ / } 1.68 \text{ tonnes}$ Fresh Water: $0.25 \text{ m}^3 \text{ / } 0.25 \text{ tonnes}$ Waste Water: $0.20 \text{ m}^3 \text{ / } 0.20 \text{ tonnes}$

Deck cargo aft (max): 1.00 tonnes Deck cargo fore (max): 1.00 tonnes

ACCOMMODATION:

Personnel: 29 (Beurteaux Krue Air Seating)

Crew:

MACHINERY & PROPULSION:

Main Engines: 2 x Caterpillar C18 TA

Total Power: 1000 BKW / 1340 BHP at 2100 rpm Twin Disk gearbox HPTO 244

Rolls Royce Waterjet FF 375S

Speed 30 Kts

Range at Max speed 210 NM

Engine Rating B - Heavy Duty, 10/12 hrs full load

3000-5000 Typical hours per year

Generators: Caterpillar Cl.5 NA, Voltage 400 V, Phase(s) 3 Frequency 50 Hz, Capacity 11.0 kW - 13.5 kVA

SAFETY EQUIPMENT:

6 x Parachute Flares Red

2 x Lifebouys 30 x Solas lifejackets 2 x 16 person Life raft

NAVIGATION/ COMMUNICATION:

Radar: 10" Furuno 1835
GPS: 4.5" LCD Furuno GP-32
Magnetic Compass: dashboard mounted
Echo Sounder: 3.5" LCD Raymarine ST60
VHF: Sailor TR6210

ADDITIONAL DATA:

Anchor: Pool TW 24KG, 3m 10mm chain + 55m 16mm Nylon line

Fixed FiFi Internal system Engine Room Novec 1230

Aft deck Sun Awning

Lifting Lugs - fore and aft / Hull and Superstructure

The Vessel specifications are reviewed and new brochures printed at regular intervals. Every endeavour has been made to provide accurate information on this brochure; however, the vessel owners do not accept any liability for errors, omissions or misprints published.